


STATE
LV

**WELL LOG AND REPORT TO THE STATE ENGINEER
OF NEVADA**

Log No. 60641
 Rec.....
 Well No.....
 Permit No.....



PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Do not fill in.

Owner Roy Thrush Driller S. R. McKinney & Sons, Inc.

Address 6060 East LaMadre, Las Vegas Address 1042 S. Main St. L. Vic. No. 45

Location of well: NE 1/4 SW 1/4 Sec. 36, T. 19N/S, R. 60E, in Clark County

or.....

Water will be used for Domestic Total depth of well 250 feet.

Size of drilled hole 12" to 50 ft., 10" to 250 Weight of casing per linear foot XX10 gauge

Thickness of casing 10 gauge Temp. of water.....

Diameter and length of casing 8 5/8 inch to 250 ft.

(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 65 ft.

If flowing well describe control works.....

(Type and size of valve, etc.)

Date of commencement of well 1-20-64 Date of completion of well 1-24-64

Type of well rig Bucyrus Erie 22 W. Cable tools.

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	2	2	sandy soil
2	15	13	caliche
15	27	12	soft caliche
27	37	10	brown clay
37	92	55	sandy brown clay
92	105	13	brown clay and gravel streaks
105	125	20	gravelly clay Water
125	145	20	brown clay and gravel streaks
145	150	5	gravel water
150	165	15	brown clay
165	192	27	brown clay with gravel streaks
192	208	16	gravel water
208	237	29	clay and gravel streaks, water
237	250	13	gravelly clay Water

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 192 to 250 ft.

Other aquifers 125 to 145

92 to 105

First water at 105 feet.

Casing perforated

from 100 to 250 ft.

Size of perforations

3/16" X 10"

RECEIVED

JUL 30 1971

DIV. OF WATER RESOURCES
 BRANCH OFFICE
 LAS VEGAS, NEVADA

