WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 61583
Rec. 11/10 1947
Well No.
Permit No. 12282
Do not fill in

Owner Jay Robb Driller Harry Wilson & Preston Bradshaw

Address Glendale, Nev. Address Cedar City, Utah Lic. No. 43

Location of well: N.E. Cor. ¼ S.E. ¼ Sec. 35, T. 14 N/S, R. 66 E, in Clark County

or

Water will be used for Ind. Well Total depth of well 118 ft.

Size of drilled hole 16" Weight of casing per linear foot 50 #

Thickness of casing 1/4" Temp. of water Cold

Diameter and length of casing 6 1/2" 48 ft. of casing in well
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 15 ft.

If flowing well describe control works.
(Type and size of valve, etc.)

Date of commencement of well Oct. 20, 1947 Date of completion of well Oct. 25

Type of well rig 240 Star - Cable tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	18	18	Clay
18	28	10	Sand
28	30	2	Sand & Gravel
30	47	17	Sand
47	52	5	Gravel
52	62	10	Sand
62	88	6	Gravel
88	94	6	Sandy Clay
94	118	24	Clay

Water-bearing Formation, Casing, Perforations, Etc.

Chief aquifer (water-bearing formation)

from 62 to 88 ft.

Other aquifers 47 to 52

First water at 28 feet.

Casing perforated

from 65 to 88 ft.

Size of perforations

1/2" by 4"

(OVER)

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
16 1/2"	0	98	98	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Reported well will produce 1400 gpm - 60' drawdown.
Water hard but suitable for irrigation (By letter 7/7/47)

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Harry Wilson & Preston Bradley
Well Driller

By Harry Wilson

License No. 43

Dated Nov 6, 1947

(Not to be filled in by Driller)