RECEIVED
MAY 1 1968
DIV. OF WATER RESOURCES
BRANCH OFFICE
LAS VEGAS, NEVADA

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 61745
Rec.
Well No.
Permit No.
Do not fill in.

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Owner: Merle Musgrove Driller: Chas. Nyberg

Address: Box 285 Pahrump Address: Box 214 Pahrump Lic. No. 418

Location of well: NE ¼ SE ¼ Sec. 16, T. 19 N/S, R. 53 E, in Nye County

or

Water will be used for: domestic Total depth of well: 130'

Size of drilled hole: 12" Weight of casing per linear foot: 12 lbs

Thickness of casing: 10 gauge Temp. of water

Diameter and length of casing: 8" casing 130'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface: 27'

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well: April 16, 1968 Date of completion of well: April 24, 1968

Type of well rig: Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	12	12	surface
12	29	17	brown clay
29	33	4	caliche
33	62	29	brown clay
62	66	4	caliche
66	92	26	brown clay
92	95	3	caliche
95	105	10	soft sandy clay
105	130	25	brown clay

(OVER)

Water-bearing Formation, Casing Perforations, etc.

Chief aquifer (water-bearing formation)

from 95 to 105 ft.

Other aquifers: 62-66

First water at: 35 feet.

Casing perforated

from 50 to 130 ft.

Size of perforations

3/8" wide 8" long

919

LOG OF FORMATIONS—Continued

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	REMARKS—Seals, Grouting, etc.
8"	0	130	130	well co cemented 0-50'

GENERAL INFORMATION—Pumping Test, Quality of Water, etc.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed Charles Nyberg
Well Driller

By Janet Nyberg

License No. 418

Dated April 29, 19 68

(Not to be filled in by Driller)