

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 62540
 Rec.
 Well No.
 Permit No. Contract

Do not fill in

Owner W.W. Clyde Driller Tom Miller

Address Address Lic. No. 129

Location of well: S¹/₄ SW¹/₄ Sec. 35, T2N/S, R55E, in Clark County
 or S¹/₂ of S.W. ¹/₄ NW¹/₄ Sec 35 T2N R55E Range 55E East

Water will be used for Road Construction Total depth of well 500 ft

Size of drilled hole 13 " Weight of casing per linear foot 10 gage

Thickness of casing 10 gage Temp. of water

Diameter and length of casing 8 "-497 ft.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 330 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well April 10-54 Date of completion of well May 28-54

Type of well rig 72 Spud Star Spudder

LOG OF FORMATIONS

| From feet | To feet | Thickness feet | Type of material |
|-----------|---------|----------------|--------------------------|
| 0 | 323 | 323 | Clay and Gravel |
| 323 | 336 | 13 | Water sand and Gravel |
| 336 | 355 | 19 | Clay and Gravel |
| 355 | 360 | 5 | Water Gravel |
| 360 | 370 | 10 | Clay and Gravel |
| 370 | 375 | 5 | Water gravel |
| 375 | 426 | 51 | <i>Clay & Gravel</i> |
| 426 | 432 | 6 | Sand |
| 432 | 455 | 23 | Clay and Gravel |
| 455 | 460 | 5 | Water Sand |
| 460 | 478 | 18 | Clay and Gravel |
| 478 | 485 | 7 | Water Sand |
| 485 | 500 | 15 | Clay and Gravel |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 323 to 336 ft.

Other aquifers 355-360

370 -375

426-432

455-465

478-485

First water at 323 feet.

Casing perforated

from 330 to 497 ft.

Size of perforations

1/2 x 3

LOG OF FORMATIONS—Continued

| From feet | To feet | Thickness | Type of material |
|-----------|---------|-----------|------------------|
| | | | |

CASING RECORD

| Diam. casing | From feet | To feet | Length | "Remarks"—Seals, Grouting, Etc. |
|--------------|-----------|---------|--------|--|
| 8 | 0 | 497 | 497 | Well gravel packed from 330- 497 Cemented casing 20 ft from surface |

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No.....

Dated....., 19.....

(Not to be filled in by Driller)
