WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 63004
Permit No.
Basin 090
NOTICE OF INTENT NO. 34201

1. OWNER Texaco
MAILING ADDRESS 5330 Primrose
Fair Oaks, California

ADDRESS AT WELL LOCATION 899 Tahoe Boulevard
Incline Village, Nevada

2. LOCATION ¼ SW ¼ Sec. 15 T. 16 N/S R. 18 E County
PERMIT NO. M/O 1053 (Issued by Water Resources) 132-24-4,10,11,23 (Parcel No.) (Subdivision Name)

3. WORK PERFORMED
XX New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial XX Monitor ☐ Stock

5. WELL TYPE
☐ Cable XX Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SILTY GRAVELLY SAND		0	1	
SILTY MED-FINE SAND		1	2	
SILTY SANDY GRAVEL		2	7	
GRANITE BOULDERS		7	14	
GRAVELLY SILTY SAND		14	24	
GRAVELLY SILTY MED SAND		24	28.5	
GRAVELLY MED-FINE SAND		28.5	39	
GRAVELLY SILTY MED-FINE SAND		39	44	
GRAVELLY SAND		44	51	
CLAYEY SILTY SAND		51	58	
SILTY FINE SAND		58	63	
SILTY GRAVELLY MED-FINE SAND		63	67	
CLAYEY SILTY GRAVELLY		67	71	
BOULDERS		71	82	
CLAYEY SILTY MED-FINE		82	83	
SILTY SANDY GRAVEL		83	86	
GRANITE BOULDERS		86	98	

Date started 6/6, 1996
Date completed 8/10, 1996

RECEIVED 96 AUG 14 PM 2:11 STATE ENGINEER'S OFFICE

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 98 Feet Depth Cased 98 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
6 5/8	0	98

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2		SCH 40	0	98

Perforations:
Type perforation Slot
Size perforation .020
From 68 feet to 98 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 63
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout
Gravel Packed: ☒ Yes ☐ No
From 63 feet to 98 feet

9. WATER LEVEL
Static water level 86 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Western Strata Exploration, Inc. (Contractor)
Address P.O. Box 1664 (Contractor)
West Sacramento, Ca 95691
Nevada contractor's license number issued by the State Contractor's Board 0034236A
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1937
Signed (By driller performing actual drilling on site or contractor)
Date 8/1/96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627