

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 32536  
 Santa Fe Pipeline

1. Consultant: CDM Engineers & Constructors Inc. Client: \_\_\_\_\_  
 1. OWNER \_\_\_\_\_ ADDRESS AT WELL LOCATION: \_\_\_\_\_  
 MAILING ADDRESS: 50 W. Liberty, Suite 770 Vista Canyon Group Sparks Solvent/Fuel Site  
 Reno, Nevada 89501 Sparks, Nevada  
 2. LOCATION NE 1/4 NE 1/4 Sec. 9 T. 19N N/S R. 20 E. Washoe County  
 PERMIT NO. M/O 913 A-2 34-102-14 Sparks Solvent/Fuel Site  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Lt. brown subangular to subround silty sand med. dense dry		0	11	11
with subround to sub-angular gravel @ 8ft.				
Lt. brown subangular to subround sand w/angular to subround gravel, abundant cobbles, minor silt, med. dense		11	33	22
color change to gray brown below 32ft.				
gray brown sand w/gravel abundant cobbles, minor silt, med. dense saturated below 34ft. Wet below 40ft. saturated below 43 ft. Color change to lt. brown below 50ft.				
Lt. brown sand w/ gravel abundant cobbles and minor silt, med. dense, saturated best circulation, collapsed to 78.9ft.				

8. WELL CONSTRUCTION  
 Depth Drilled 89 Feet Depth Cased 78.9 Feet  
 HOLE DIAMETER (BIT SIZE)  
 11 1/4 Inches <sup>From</sup> 0 <sup>To</sup> 89 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"	w/ cap	sch 80 PVC	0	22.6
6"		SS sump w/cap	73.5	78.9
Centralizers 73., 48., 22. ss-				

Perforations:  
 Type perforation factory sawed slot  
 Size perforation .100 slot ss wire wrapped  
 From 22.6 feet to 73.5 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Neat Cement  
 Cement Grout  
 Concrete Grout  
 Depth of Seal 3 - 17.6  
 Placement Method:  Pumped  Poured  
 Bentonite Seal: 17.6 - 19.6  
 Gravel Packed:  Yes  No 1/4-1/8" well sand  
 Filter 19.6 - 20.6 #20 feet to 20.6 - 78.9 feet

Date started 5-10-95, 19\_\_\_\_\_  
 Date completed 5-12-95, 19\_\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
no test			

9. WATER LEVEL  
 Static water level Not known feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. N/A P.S.I.  
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370  
RENO, NEVADA 89510 Contractor  
 Nevada contractor's license number 22549  
 issued by the State Contractor's Board  
 Nevada driller's license number issued by the 908  
 Division of Water Resources, the on-site driller  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date January 31, 1996