

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 32545

Consultant: CDM Engineers & Constructors Client: \_\_\_\_\_  
 1. OWNER: \_\_\_\_\_ ADDRESS AT WELL LOCATION Santa Fe Pipeline  
 MAILING ADDRESS 50 W. Liberty, Suite 770 Vista Canyon Group Sparks Solvent/Fuel Site  
Reno, Nevada 89501 Sparks, Nevada  
 2. LOCATION SE  $\frac{1}{4}$  NE  $\frac{1}{4}$  Sec. 9 T. 19N N/S R. 20 E. Washoe County  
 PERMIT NO. M/O 913 C-2 34-102-14 Sparks Solvent/Fuel Site  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED 4. PROPOSED USE 5. WELL TYPE  
 New Well  Replace  Recondition  Domestic  Irrigation  Test  Cable  Rotary  RVC  
 Deepen  Abandon  Other \_\_\_\_\_  Municipal/Industrial  Monitor  Stock  Air  Other TUBEX \_\_\_\_\_

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Lt. brown silt w/sand med. dense, dry		0	7	7
Gray brown subangular to subround sand w/ subround to angular gravel, abundant silt, minor cobbles, med. dense		7	30	23
abundant cobbles and minor silt below 15ft. color change to lt. brown below 20ft. color change to gray below 33ft.				
Lt. brown sand w/ gravel abundant cobbles and minor silt, med. dense.		30	59	29
Little or no silt below 59 ft.				
Lt. brown sand w/ gravel, abundant cobbles, med. dense, saturated		59	70	11
Note: Heaving sands from				

8. WELL CONSTRUCTION  
 Depth Drilled 70 Feet Depth Cased 58.9 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
11 1/2 Inches 0 Feet 70 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 CASING SCHEDULE  

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"	w/ cap	sch 80 PVC	0	17.7
6"		SS Sump w/cap	53.3	58.9
Centralizers		52,35,17 SS		

 Perforations:  
 Type perforation Factory sawed slot  
 Size perforation .100 slot SS wire wrapped  
 From 17.7 feet to 53.3 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 3 - 12.7  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite Seal: 12.7-14.7  
 Gravel Packed:  Yes  No 1/4-1/8" well sand  
 Filter From 14.7-15.7 #20 feet to 15.7 - 58.9 feet

Date started 5-24-95, 19\_\_\_\_\_  
 Date completed 5-25-95, 19\_\_\_\_\_

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
no test			

9. WATER LEVEL  
 Static water level not known feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. N/A P.S.I.  
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date February 5, 1996