

PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 27274

Consultant: CDM Engineers & Constructors Inc. Client: \_\_\_\_\_  
 1. OWNER: \_\_\_\_\_ ADDRESS AT WELL LOCATION: Santa Fe Pipeline  
 MAILING ADDRESS: 50 W. Liberty, Suite 770 Vista Canyon Group Sparks Solvent/Fuel Site  
Reno, Nevada 89501 Sparks, Nevada

2. LOCATION SW 1/4 NE 1/4 Sec. 9 T. 19N N/S R. 20 E. Washoe County  
 PERMIT NO. M/O 913 E-3 S. side of R.R. R/W 34-101-42 Sparks Solvent/Fuel Site  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_  
 4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock  
 5. WELL TYPE  
 Cable  Rotary  PVC  
 Air  Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown subangular to sub-round silty sand w/ angular to subround gravel, occasional cobbles, med. dense, dry		0	30	30
Color change to gray brown, abundant cobbles and silt below 10ft.				
Minor silt below 20ft.				
Saturated below 29.5 ft.				
Gray brown sand w/ gravel abundant cobbles and minor silt.		30	59.2	29.2
Color change to lt. brown at 45ft.				

8. WELL CONSTRUCTION  
 Depth Drilled 59.2 Feet Depth Cased 58 Feet  
 HOLE DIAMETER (BIT SIZE)  
 From To  
11 1/4 Inches 0 Feet 59.2 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"	w/cap	SCH 80 PVC	0	16.7
6"		SS Sump w/cap	52.6	58.
Centralizers		52,34,16 SS		

Perforations:  
 Type perforation Factory sawed slot  
 Size perforation 100 slot SS wire wrapped  
 From 16.7 feet to 52.6 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 3 - 11.7  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout  
 Bentonite Seal: 11.7 - 13.7  
 Gravel Packed:  Yes  No 1/4-1/8" well sand  
 Filter From 13.7 - 14.7 #20 feet to 14.7 - 59.2 feet

9. WATER LEVEL Well Sand  
 Static water level: not known feet below land surface  
 Artesian flow \_\_\_\_\_ G.P.M. N/A P.S.I.  
 Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name WAYNE DRILLING, INC. Contractor  
 Address P.O. BOX 12370 Contractor  
RENO, NEVADA 89510  
 Nevada contractor's license number issued by the State Contractor's Board 22549  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908  
 Signed [Signature] By driller performing actual drilling on site or contractor  
 Date February 6, 1996

Date started 5-8-95, 19\_\_\_\_\_  
 Date completed 5-9-95, 19\_\_\_\_\_

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test			