

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 27267

Consultant: CDM Engineers & Constructors Inc. Client: Santa Fe Pipeline
 MAILING ADDRESS 50 W. Liberty, Suite 770 ADDRESS AT WELL LOCATION Vista Canyon Group Sparks Solvent/Fuel Site
Reno, Nevada 89501 Sparks, Nevada
 2. LOCATION NE $\frac{1}{4}$ NW $\frac{1}{4}$ Sec 9 T 19N N/S R 20 E Washoe County
 PERMIT NO. M/O 913 H-3 N. Side R.R. R/W 32-220-62 Sparks Solvent/Fuel Site
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC
 Deepen Abandon Other Municipal/Industrial Monitor Stock Air Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Brown subangular to sub-round sand w/angular to sub round gravel, abundant cobbles, med. dense, moist		0	30	30
Saturated, color change to lt. brown, saturated below 30ft.				
Lt. brown sand w/gravel and abundant cobbles, med. dense, saturated		30	58.7	28.7

8. WELL CONSTRUCTION
 Depth Drilled 58.7 Feet Depth Cased 56 Feet
 HOLE DIAMETER (BIT SIZE)
 From 11 1/2 Inches To 0 Feet 58.7 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6"	w/cap	SCH 80 PVC	0	14.6
6"		SS Sump w/cap	49.6	56
Centralizers		49.5, 33, 18 SS		

Perforations:
 Type perforation Factory sawed slot
 Size perforation 100 Slot SS wire wrapped
 From 14.6 feet to 49.6 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type: Neat Cement Cement Grout Concrete Grout
 Depth of Seal 3 - 10.7
 Placement Method: Pumped Poured
 Bentonite Seal: 10.7 - 12.4
 Gravel Packed: Yes No 1/4-1/8" well sand
 Filter From 12.4-13.5 #20 feet to 13.5-58.7 feet

9. WATER LEVEL
 Static water level not known feet below land surface
 Artesian flow _____ G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

Date started 4-11-95, 19____
 Date completed 4-12-95, 19____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
no test			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908
 Signed Larry C. Helman By driller performing actual drilling on site or contractor
 Date February 7, 1996