WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 63426
Permit No.
Basin 083

NOTICE OF INTENT NO. 30596

Consultant:
1. ~~OWNER~~ CSA, INC.
MAILING ADDRESS P.O. Box 7475
Reno, Nevada 89510

Owner:
ADDRESS AT WELL LOCATION AGE Corporation
P.O. Box 1546
Sparks, Nevada 89431

2. LOCATION Basin 1/4 #83 1/4 Sec. 16 T. 19N N/S R. 21E E. Storey County
PERMIT NO. W-443-A 61608 (Issued by Water Resources) | Parcel No. | Lockwood Trailer Park, Lockwood, NV (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen & ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sluff broken rock w/clay		0	14	14
Gray rock (very hard)		14	19	5
Brown rock broken & fractured		19	22	3
Brown clay w/rock		22	33	10
Brown clay more rock		33	41	8
Dark gray weathered rock		41	52	11
Orangish brown clay w/rock		52	58	6
Dark gray volcanic rock,hard		58	70	12
Brown clay		70	79	9
Tan clay		79	89	10
Gray rock		89	95	14
Lt. gray rock		95	130	35
Gray rock broken & fractured	X	130	157	27
Hint of purple, stop drilling		157	160	17
4-8-96				
Test Hole Abandonment.				
Tremie pipe & pressure				
pump. 34 SKS. Neat cement				
filling bore hole from				
bottom of top.				

Date started 4-3-96, 19
Date completed 4-8-96, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 160 Feet Depth Cased Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6½" Inches	0 Feet	160 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)

Perforations:
Type perforation
Size perforation
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☐ Yes ☐ No
Depth of Seal
Placement Method: ☐ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☐ Yes ☐ No
From feet to feet

9. WATER LEVEL
Static water level 66.9 feet below land surface
Artesian flow G.P.M. 40 P.S.I.
Water temperature °F Quality water quality poor, abandon test hole

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed (By driller performing actual drilling on site or contractor)
Date April 10, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627