

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 63787  
 Rec. No. \_\_\_\_\_ 19\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. DOM  
*Do not fill in*

Owner H. M. Millet Driller Effinger Drill & Pump Serv.

Address 1209 Webb Street Address Box 589 Lic. No. 212

Location of well: SW 1/4 NW 1/4 Sec. 24, T. 20 N/S, R. 53 E, in Nye County

Water will be used for Domestic Total depth of well 200 feet

Size of drilled hole 14 inch Weight of casing per linear foot \_\_\_\_\_

Thickness of casing 1255 Temp. of water \_\_\_\_\_

Diameter and length of casing 10 3/4 OD 180 feet 25' 8" ID Liner .250 wall  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_

If nonflowing well give depth of standing water from surface 35'7" from top of casing

If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)

Date of commencement of well February 26, 1958 Date of completion of well March 7, 1958

Type of well rig "71 Speed Star"

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	13	13	Sandy Gravel
13	52	39	Yellow Clay
52	53	1	Gravel (Water)
53	91	38	Yellow Clay
91	200	109	Gravel (Water)

RECEIVED  
 APR 11 58  
 STATE ENGINEER

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)

from 91 to 200 ft.

Other aquifers 52-53

---

52

First water at \_\_\_\_\_ feet.

---

Casing perforated

from 50 to 200 ft.

---

Size of perforations

1/8" x 15"