

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 21668

Consultant:

1. OWNER EBASCO ENERASTRUCTURE ADDRESS AT WELL LOCATION SIERRA PACIFIC POWER CO.
 MAILING ADDRESS 2525 Natomas Park Dr. Suite 250 Tracy Clark Power Station
Sacramento, Ca. 95833-2900 I-80 East, Sparks, Nevada

2. LOCATION NW 1/4 NE 1/4 Sec. 33 T. 20N N/S R. 22E E Storey County
 PERMIT NO. M/O 381-A MW 9 04-091-11 N of Evaporation Pond & N of RR tracks
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Surface is boulders and gravelly FILL from pond excavations		0	3	3
Dark brown, rel. loose SANDY GRAVEL		3	7	4
Less sand, cuttings are frags w/some whole pebbles		7	10	3
Becoming sandier		10	13	3
Less sandy		13	15	2
Slight coating of frags by silts or clays		15	18	3
Grades to dark brown. Moist, SILTY FINE SAND, mod. dense		18	20	2
Sand contains minor gravels		20	25	5
Gravel content starting to increase		25	27	2
Grades to SILTY SANDY GRAVEL.		27	30	3
Grades to brown SILTY SAND w/ gravel, mod. dense		30	35	5
Grades to rel. clean GRAVEL, some fines coating frags and pebbles		35	40	5
Cuttings saturated		40	44	4
Grades to SILTY SANDY GRAVEL		44	44.9	9

8. WELL CONSTRUCTION
 Depth Drilled 44.9 Feet Depth Cased 43.8 Feet

HOLE DIAMETER (BIT SIZE)
 From 7 1/2 Inches To 44.9 Feet
 _____ Inches _____ Feet
 _____ Inches _____ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" PVC		sch 40	0	43.8

Bottom cap, Locking cap, Flush cover
 Stainless Steel Centralizers @ 28' & 43'

Perforations:
 Type perforation Factory sawed slot
 Size perforation 0.02
 From 28.8 feet to 43.8 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 24.8
 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Bentonite Seal: 24.8 - 26.8
 Gravel Packed: Yes No #3 Lone Star Sand
 From 26.8 feet to 44.9 feet

9. WATER LEVEL
 Static water level 31.8 feet below land surface
 Artesian flow _____ G.P.M. N/A P.S.I.
 Water temperature N/A °F Quality N/A

Date started 3-29-93, 19_____
 Date completed 3-29-93, 19_____

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			
No test			
Well information recieved via FAX 6-9-96			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC.
Contractor
 Address P.O. BOX 12370
Contractor
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 908

Signed [Signature]
 By driller performing actual drilling on site or contractor

Date June 12, 1996