

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY
Log No. 64205/64206
Permit No. _____
Basin 061

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 25578

1. OWNER BARRICK GOLDSTRIKE ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE
 MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

2. LOCATION SW 1/4 NW 1/4 Sec. 29 T. 36 N. R. 50 E. EUREKA County
 PERMIT NO. M/O-441A Parcel No. N/A Subdivision Name N/A
Issued by Water Resources

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other.....

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
LOOSE FILL & DUMP MATERIAL		0	36	36
SAND & GRAVELS		36	65	29
GRAY SAND		65	90	25
BROWN SAND		90	145	55
CARLIN SILTSTONE	1 GPM	145	175	30
CARLIN GRAVELS	10GPM	175	300	125
BROWN CLAY	20GPM	300	420	120
YELLOW-BROWN SAND & CLAY	20 GPM	420	490	70
GRAY-BLACK ROCK	20GPM	490	560	70
BEDROCK VINNINI				
BLACK ROCK, SOME FRACTURES, CLAYS & OXIDATION	40GPM	560	800	240

8. WELL CONSTRUCTION
 Depth Drilled 800 Feet Depth Cased 450 Feet

HOLE DIAMETER (BIT SIZE)
 From To
12-1/4 Inches 0 Feet 40 Feet
6-1/4 Inches 40 Feet 800 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7	2.4	.300	0	40
1.3	2.7	.085	0	277
1.3	2.7	.085	0	430

Perforations:
 Type perforation MILL SLOT
 Size perforation .125 INCH
 From 277 feet to 297 feet
 From 430 feet to 450 feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 51 FEET Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 268/424 feet to 298.5/452 feet

Date started SEPTEMBER 15 19 96
 Date completed SEPTEMBER 20 19 96

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
SHALLOW STRING	45	MIN - 1/2 GPM	

9. WATER LEVEL
 Static water level 0-DRY/5-262 feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature 70 °F Quality FAIR

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING Contractor
 Address 2286 WEST 1500 SOUTH Contractor
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1773

Signed MARK WAITE By driller performing actual drilling on site or contractor
 Date 9-17-96

RECEIVED
96 OCT 18 PM 2:38
STATE ENGINEERS OFFICE