WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

#96-035-00
STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 6424
Permit No.
Basin

NOTICE OF INTENT NO. 32511

1. OWNER Firstmiss Gold, Inc.
MAILING ADDRESS P.O. Box, 220
GOLCONDA, NV. 89414

ADDRESS AT WELL LOCATION
GETCHEL MINE SITE

2. LOCATION SE ¼ NE ¼ Sec. 33 T 39 N/S R 42 E Humboldt County
PERMIT NO. N-0-993-A-AMENDED (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
DUMP TAILINGS		0	40	40
CHERT		40	100	60
BASALTS		100	500	400
WHITE TUFF		500	595	95
HORNFELL, SKARN		595	985	390
DIKE		985	995	10
HORNFELL SKARN		995	1090	95
DACITE DIKE		1090	1110	20
HORNFELL, SKARN		1110	1250	140
DIKE		1250	1270	20
HORNFELL		1270	1320	50
BASALTS		1320	1500	180
HORNFEL, SKARN		1500	1715	215
DIKE		1715	1720	5
HORNFELL, SKARN		1720	2380	660
BLACK BROWN				
DIKE		2380	2405	25
HORNFEL		2405	2554	149

Date started MARCH 25, 19 96
Date completed JUNE 6, 19 96

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
4.5		4 1/2 HOURS

8. WELL CONSTRUCTION
Depth Drilled 2554 Feet Depth Cased 1000 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 7/8 Inches	0 Feet	20 Feet
6 5/8 Inches	20 Feet	800 Feet
3 7/8 Inches	800 Feet	2554 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6	17	.250	0	20
4	10.8	.237	0	800
1 1/7	2.4	.140	0	800

Perforations:
Type perforation MILL SLOT
Size perforation .125
From 800 feet to 1000 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 56 Feet
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 770 feet to 1025 feet

9. WATER LEVEL
Static water level 354 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature cool °F Quality Fair

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1773

Signed Mark Waite (By driller performing actual drilling on site or contractor)
Date 6-6-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627