WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64293
Permit No.
Basin 102

NOTICE OF INTENT NO. 32670

1. OWNER Dale Dynehart
MAILING ADDRESS
ADDRESS AT WELL LOCATION 8245 Brooklin SS NV 89403

2. LOCATION ¼ NE ¼ Sec. 21 T 17 N/S R 25 E/W County
PERMIT NO. N/A (Issued by Water Resources) | 17-503-09 (Parcel No.) | Subdivision Name

3. WORK PERFORMED: [X] New Well [ ] Replace [ ] Recondition [ ] Deepen [ ] Abandon [ ] Other
4. PROPOSED USE: [X] Domestic [ ] Irrigation [ ] Test [ ] Municipal/Industrial [ ] Monitor [ ] Stock
5. WELL TYPE: [ ] Cable [X] Rotary [ ] RVC [ ] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Sand | | 0 | 12 | 12 |
| Sandy Gravels | | 12 | 30 | 18 |
| Gravels | | 30 | 60 | 30 |
| Gravels Clay | | 60 | 83 | 23 |
| Clay Grey | | 83 | 94 | 11 |
| Clay Blue | | 94 | 115 | 21 |
| Coarse Gravels | | 115 | 123 | 18 |

Date started 2/13/96, 19
Date completed 2/14/96, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 60-65 gpm | | |

8. WELL CONSTRUCTION
Depth Drilled 123 Feet Depth Cased 124' Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 16 5/8 | Inches | 1 Feet | 123 Feet |
| | Inches | Feet | Feet |
| | Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 16 5/8 | 13. | 1.88 | +1 | 123 |
| | | | | |

Perforations:
Type perforation Torch Cut
Size perforation 3/16 x 60 x 6" nominal pipe
From 118 feet to 122 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50'
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 123' feet

9. WATER LEVEL
Static water level 41' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature C °F Quality V. Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Jason Drilling Inc (Contractor)
Address P.O. 599 (Contractor)
SS NV 89426
Nevada contractor's license number issued by the State Contractor's Board 0031844
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1826
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 2/14/96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627