Log No. 64309
Rec. 8/8/54 19
Well No.
Permit No.
Do not fill in

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Owner: Primm Investment Co. Driller: Roscoe Moss

Address: Gardena, Calif. Address: 4360 No. Worth St. L.A. Calif. Lic. No. 8

Location of well: ____ ¼ ____ ¼ Sec. 5, T. approx 27 S, R. 59 E, in Clark County

or

Water will be used for: Total depth of well: 748'

Size of drilled hole: 10" Weight of casing per linear foot:

Thickness of casing: 5/16" Temp. of water:

Diameter and length of casing: 16" I.D. & 12¾ O.D.
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface:

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: June 24, 1954 Date of completion of well: Aug. 3, 1954

Type of well rig:

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
671	700	29.	Partially decomposed granite.
700	740	40	Sandy yellow Clay & Granite Rock
740	748	8	Sand & Gravel to 6" some Clay.
			12." Casing was collapsed from 582' to 660'. Started swedging with 8" swedge and increased to size 12". Went outside pipe at 615', drilling up and passed bottom 46', drilled to 748 ft. pulled out 12" casing. Water raised 5' when well was bailed with scow.

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from ____ to ____ ft.

Other aquifers

First water at 103 feet.

Casing perforated

from ____ to ____ ft.

Size of perforations

(OVER)

910