

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. **64314**
 Rec. 19
 Well No.
 Permit No.
Do not fill in

Owner Primm Investment Company Driller Roscoe Moss Company

Address Gardena, California Address Los Angeles, California Lic. No.

Location of well: NW $\frac{1}{4}$ NE $\frac{1}{4}$ Sec. 26, T27N/S, R59E, in Clark County, County
or

Water will be used for Total depth of well 555

Size of drilled hole 12-3/4" Weight of casing per linear foot

Thickness of casing 1/4" Temp. of water 68 degrees

Diameter and length of casing 12-3/4" O.D. 1/4" wall
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 130

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well 10-26-56 Date of completion of well 1-4-56

Type of well rig Calif Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8		Brown clay
8	28		Caliche
28	158		Caliche and gravel
158	270		Brown clay and gravel
270	273		Red clay
273	300		Sticky brown clay and some gravel
300	392		Brown clay and gravel
392	498		Brown clay and broken rock
498	555		Volcanic rock

RECEIVED
 OCT 27 1956
 STATE ENGINEER
 LAS VEGAS

Water-bearing Formation, Casing Perforations, Etc.

Not perforated.

Chief aquifer (water-bearing formation)

from to ft.

Other aquifers

First water at 130 feet.

Casing perforated
Not perforated

from to ft.

Size of perforations
