

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 34193

1. Consultant: ERM-West, Inc. Client: Kaiser Micro Mill
 1. OWNER: ERM-West, Inc. ADDRESS AT WELL LOCATION: Near Tracy
 MAILING ADDRESS: 455 Capitol Mall, Suite 800
Sacramento, CA 95814 Sparks, NV
 2. LOCATION: N 1/4 SE 1/4 Sec 32 T 20N N/S R 22 E Storey County
 PERMIT NO. M/O 1087 MW#-1 1-A 4-091-27 East of Sparks, NV.
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand, brown, loose, well-graded		0	3	3
Gravelly sand, grey & brown, coarse gravel dia. ≤ 2"		3	9	6
Sand gravel, brown & grey, coarse gravel dia. ≤ 2"		9	21	11
Gravel & cobbles, grey, coarse gravel dia. ≤ 2"		21	30	9
Sandy gravel, brown & grey, coarse gravel dia. ≤ 3", sand large grained		30	36	6
Gravel & cobbles, grey coarse particle dia. as large as 24" trace amounts of large-grained sand		36	49	13
Gravelly sand, grey & brown, coarse, large grained		49	59	10

8. WELL CONSTRUCTION
 Depth Drilled 59 Feet Depth Cased 59 Feet
 HOLE DIAMETER (BIT SIZE)
 From 10 Inches To 59 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet
 CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" ID		Sch 80 PVC	0	39

 PVC Locking Cap / Steel Monument 8" x 5"
 SS Centralizers at 17', 36', 54' End Cap
 Perforations:
 Type perforation factory sawed slot
 Size perforation 0.020 inch
 From 39 feet to 59 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet
 Surface Seal: Yes No Seal Type:
 Depth of Seal 4' concrete / 4-33 ft Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Bentonite Seal: 35 - 35 feet
 Gravel Packed: Yes No
 From 35 feet to 59 feet

Date started 10-31-96, 19____
 Date completed 11-01-96, 19____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
No test			

9. WATER LEVEL
 Static water level 43 feet below land surface
 Artesian flow _____ G.P.M. N/A P.S.I.
 Water temperature not known Quality not known

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370
RENO, NEVADA 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, on-site driller 908
 Signed [Signature]
 by driller performing actual drilling on site or contractor
 Date December 16, 1996

RECEIVED
 JAN 13 PM 2:41
 WATER RESOURCES OFFICE