WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64581
Permit No.
Basin 131

NOTICE OF INTENT NO. 21149

1. OWNER Battle Mt. Gold
MAILING ADDRESS Copper Basin Rd Battle Mountain
ADDRESS AT WELL LOCATION South of Tailing Impoundment

2. LOCATION SE ¼ SW ¼ Sec. 9 T. 30-N N/S R. 43 E. Lander County
PERMIT NO. MO 967C (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☒ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand Gravel Clay		0	120	120'
Gravel + Sand + Water	20gpm	120	160	40
Locking Cap	40 to	160	280	
PVC Stickup	50gpm			120
Ground Surface				
Cement				
50'				
Bentonite				
57' Top of				
Sand Pack				
2" Seed 80				
PVC Blank				
67'				
Top of Screen				
180' of				
2" OD PVC				
Seed 80 Screen				
with .020				
Slots				
Bottom of				
Screen 247'				
10 Blank 2"				
OD PVC				
23' Caved in				

2" PVC Blank
257'
280'

Date started 1-24-96, 19 96
Date completed 1-28, 19 96

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
40-50		15-20 min.
NO Development		

8. WELL CONSTRUCTION
Depth Drilled 280 Feet Depth Cased 257' Feet

HOLE DIAMETER (BIT SIZE)

	From	To
12 Inches	0 Feet	20 Feet
6 1/4 Inches	20 Feet	280' Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8 5/8	24.70	0.277	12'	20'
2" OD		Sced 80	12'	257'

Perforations:
Type perforation 2" O.D. PVC Sced. 80 (Screen) with
Size perforation .020 Slots
From 67' feet to 247 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 120' feet to 280' feet

9. WATER LEVEL
Static water level 87' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name O'Keefe Drilling (Contractor)
Address P.O. Box 3810 Butte Mt. 59702 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board C-23-00-30581
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1703
Signed Frank Cook (By driller performing actual drilling on site or contractor)
Date Feb 5-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627