WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64674
Permit No.
Basin 071

NOTICE OF INTENT NO. 35850

1. OWNER Rich Brown
MAILING ADDRESS 3565 Brown Lane
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
4635 Cowboy Road
Winnemucca, NV 89445

2. LOCATION SW 1/4 SE 1/4 Sec. 7 T 35 N/S R 38 E Humboldt County
PERMIT NO. (Issued by Water Resources) | Parcel No. 10-484-35 | Subdivision Name Lot 9BB

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	7	7
Gravel & Cobbles		7	88	81
Gravel & Cobbles w/Clay		88	102	14
Fractured Rock		102	112	10
Hard Rock		112	121	9
Gravel & Cobbles		121	140	19
Fractured Rock w/Clay		140	162	22
See next line		162	207	45
Fractured Rock w/Sand & Gravel				

Date started 2/23/97, 19__
Date completed 2/25/97, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		2 hr.

8. WELL CONSTRUCTION
Depth Drilled 207 Feet Depth Cased 190 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 7/8 Inches		0 Feet	207 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8		.188	+1	190

Perforations:
Type perforation Single Row Mill Slot
Size perforation 1/8" x 3"
From 150 feet to 190 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 190 feet

9. WATER LEVEL
Static water level 152 feet below land surface
Artesian flow 0 G.P.M. 0 P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562

Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 2-25-97