WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64675
Permit No.
Basin 071

NOTICE OF INTENT NO 35846

1. OWNER Rich Brown
MAILING ADDRESS 3565 Brown Lane
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
Corner of Corner of Cowboy & Davey Rd.
Winnemucca, NV 89445

2. LOCATION SW 1/4 SE 1/4 Sec. 7 T 35 N/S R 38 E Humboldt County
PERMIT NO. (Issued by Water Resources) 10-484-34 (Parcel No.) Lot 9BA (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	5	5
Gravel & Cobbles		5	48	43
Clay		48	57	9
Fractured Rock		57	123	66
Gravel & Cobbles		123	160	37
Fractured Rock w/sand		160	190	30

Date started 2/10/97, 19__
Date completed 2/12/97, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
20		2 hr.

8. WELL CONSTRUCTION
Depth Drilled 207 Feet Depth Cased 190 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 7/8	Inches	0	Feet	190	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	175

Perforations:
Type perforation Single Row Mill Slot
Size perforation 1/8" x 3"
From 135 feet to 174 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 190 feet

9. WATER LEVEL
Static water level 148 feet below land surface
Artesian flow 0 G.P.M. 0 P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562

Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 2-25-97