VD-96-6

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64704
Permit No.
Basin OGL

NOTICE OF INTENT NO. 29445

1. OWNER BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION NW ¼ NW ¼ Sec. 29 T 36 N/S R 50 E EUREKA County
PERMIT NO. 58355 Issued by Water Resources | N/A Parcel No. | N/A Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[X] Municipal/Industrial [ ] Monitor [ ] Stock
MINING

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| CLAYS, SANDS, GRAVELS | | | | |
| CARLIN FORMATION | | 0 | 475 | 475 |
| BLACK ROCK WITH CLAYS | | 475 | 810 | 335 |

Date started DECEMBER 11, 1996
Date completed DECEMBER 17, 1996

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| 7.5 | | 1/4 |
| 12 | | 1/2 |
| 10 | | 3/4 |
| 8 | 263 | 1 |

8. WELL CONSTRUCTION
Depth Drilled 810 Feet Depth Cased 798.2 Feet

HOLE DIAMETER (BIT SIZE)

| | | From | To |
|---|---|---|---|
| 14-3/4 Inches | | 0 Feet | 20 Feet |
| 7-7/8 Inches | | 20 Feet | 810 Feet |
| Inches | | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 10.75 | 28 | .250 | 0 | 20 |
| 4.5 | 10 | .233 | +2 | 117.8 |

Perforations:
Type perforation MILLED SLOT
Size perforation .125
From 117.8 feet to 798.2 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100.1
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100.1 feet to 810 feet

9. WATER LEVEL
Static water level 204 feet below land surface
Artesian flow NO G.P.M. N/A P.S.I.
Water temperature 65 °F Quality FAIR

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2039

Signed DENNY ROBBLEE (By driller performing actual drilling on site or contractor)
Date DECEMBER 17, 1996

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627