WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 64782
Rec. May 9 57
Well No.
Permit No 20067
Do not fill in

Owner: F. E. Wadsworth
Driller: Darell Free
Address: Panaca, Nevada
Address: Box 1 - Ely, Nevada Lic. No. 30
Location of well: S.E.¼ S.E.¼ Sec. 18, T. 2 N/S, R. 68 E, in Lincoln County
or

Water will be used for: Irrigation
Total depth of well: 184
Size of drilled hole: 14"
Weight of casing per linear foot
Thickness of casing: 12 gauge
Temp. of water
Diameter and length of casing: 14" 184'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure
If nonflowing well give depth of standing water from surface: 7' 4"
If flowing well describe control works
(Type and size of valve, etc.)
Date of commencement of well: April 12, 1957
Date of completion of well: April 30, 1957
Type of well rig: Churn Drill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	sandy silt
25	32	7	blue clay
32	58	26	fine sand
58	61	3	sand
61	78	17	stratified fine sand + clay
78	89	11	sand
89	112	23	gravel
112	148	36	clay
148	184	36	gravel

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 148 to 184 ft.
Other aquifers: 89 to 112 ft

First water at 10 feet.

Casing perforated
from 16 to 184 ft.

Size of perforations
5/32 x 1 1/2

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

8" gravel pack hole drilled 107' filled with gravel plus 1/2-1" consuming approx 11 yds.

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By Darell Free

License No. 30

Dated April 30, 1957

OFFICE
STATE ENGINEER

1957 MAY 6 AM 8 47

(Not to be filled in by Driller)