LOG FOR ABANDONED WELL

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64834
Permit No.
Basin 212

NOTICE OF INTENT NO. 15881

1. OWNER National Groundwater Assos.
MAILING ADDRESS 601 Dempsey Rd. Westerville, OH. 43081
ADDRESS AT WELL LOCATION Vacant Lot Riviera Blvd. and Paradise Road, Las Vegas, Nv.

2. LOCATION E ½ of Sec 9 and West ½ Sec 10 T 21 N/S R 61 E CLARK County
PERMIT NO. N/A (Issued by Water Resources) #2 (Parcel No.) Sheraton ITT Gaming Div (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy Silt		0	4	4
Caliche		4	5	1
Sandy Silt		5	11	6
Caliche		11	12	1
Sandy Silt		12	21	9
Sandy-Clayey Silt		21	38	17

Abandon on April 2, 1997
Overdrilled to 38 feet
Removed All PVC Casing
Pumped Concrete Grout From
Bottom of hole to Surface

I.D. Workshop Wells No. 7 & 2
Installed and Removed
10 feet Apart

Date started March 31, 1997
Date completed April 2, 1997

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Not	Tested		

8. WELL CONSTRUCTION
Depth Drilled 38 Feet Depth Cased 38 Feet

HOLE DIAMETER (BIT SIZE)
12 Inches From ∅ Feet To 38 Feet
Inches Feet Feet
Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4 in	PVC	Sch. 40	0	38

Perforations:
Type perforation Machine Slotted
Size perforation .02
From 38 feet to 18 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0 to 15
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☐ Cement Grout ☒ Concrete Grout ☒ Bentonite Grout
Gravel Packed: ☒ Yes ☐ No
From 15 feet to 38 feet

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow ∅ G.P.M. P.S.I.
Water temperature N/A °F Quality N/A

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Gregg Drilling and Testing (Contractor)
Address 2747 Walnut Ave. (Contractor)
Signal Hill, Ca. 90806
Nevada contractor's license number issued by the State Contractor's Board 0038113
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2065
Signed David T. Meyer (By driller performing actual drilling on site or contractor)
Date 4/28/97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627