

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 32526

1. OWNER D.W. DINKENS ADDRESS AT WELL LOCATION _____
 MAILING ADDRESS 142 West 2nd Street 335 Cabrillo Lane
Reno, Nevada 89501 Sparks, Nevada 89436
 2. LOCATION NW 1/4 NW 1/4 Sec. 1 T 21N N/S R 20 E Washoe County
 PERMIT NO. 076-282-11 Spanish Springs
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____
 4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock
 5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill gravels, sand & boulders		0	5	5
Boulders gravel with gray clay		5	51	45
Reddish brown volcanic rock		51	139	88
Brown volcanic rock		139	198	59
Brown clay		198	202	4
Yellow clay		202	241	39
Green clay		241	251	10
Light brown clay		251	311	60
Green volcanic rock		311	389	78
Gray volcanic rock		389	399	10
Fracture weathered rock		399	417	18
Fracture, gray granite		417	517	100
Gray granite		517	542	25
Fracture (app 2GPM)	X	542	543	1
Gray granite		543	568	25
Green granite		568	571	3
Gray granite		571	594	23
Black granite		594	610	16
Fracture black rock	X	610	640	30
Black granite		640	660	20
Fracture broken rock		660	712	52
Black hard rock		712	727	15
Bore hole very unstable, caved in to 665 feet				

8. WELL CONSTRUCTION
 Depth Drilled 727 Feet Depth Cased 665 Feet
 HOLE DIAMETER (BIT SIZE)

	From	To
10 Inches	0 Feet	50 Feet
8 5/8 Inches	50 Feet	527 Feet
6 1/8 Inches	527 Feet	727 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	527
5" OD		.188	445	665

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 465 feet to 485 feet
 From 525 feet to 545 feet
 From 585 feet to 605 feet
 From 645 feet to 665 feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50 feet Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No
 From 50 feet to 527 feet

9. WATER LEVEL
 Static water level 420 feet below land surface
 Artesian flow G.P.M. 15 P.S.I.
 Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510
 Nevada contractor's license number issued by the State Contractor's Board 22549
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
 Signed [Signature]
 By driller performing actual drilling on site or contractor
 Date June 5, 1996

Date started 5-28-96 19
 Date completed 6-4-96 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>15</u>		