WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64964
Permit No.
Basin 0192A

NOTICE OF INTENT NO. 30651

1. OWNER MARK S. WHITNEY
MAILING ADDRESS P.O. Box 5354
Reno, Nevada 89513

ADDRESS AT WELL LOCATION
1240 Argossy Road
Reno, Nevada 89506

2. LOCATION NE ¼ NE ¼ Sec. 24 T. 22N N/S R. 18 E. Washoe County
PERMIT NO. (Issued by Water Resources) 079-362-05 (Parcel No.) Red Rock Estates (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Brown sandy clay		2	11	9
Brown fine sand		11	13	2
Decomposed granite cemented with brown clays		13	46	33
Weathered granite boulder		46	48	2
Decomposed granite cemented with brown clays		48	93	45
Soft zone, granite sands (NO WATER)		93	104	11
Weathered granite		104	153	49
Soft zone (NO WATER)		153	155	2
Weathered granite with clay streaks		155	173	18
Soft zone, broken and fractured granite	X	173	231	58
Weathered granite		231	250	19

Date started 11-4-96, 19
Date completed 11-5-96, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	100 Feet
8 5/8 Inches		100 Feet	250 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	250

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 180 feet to 240 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100 feet
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100 feet to 250 feet

9. WATER LEVEL
Static water level 123 feet below land surface
Artesian flow G.P.M. 12 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date November 6, 1996

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627