Revised Parcel Location

WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64988
Permit No.
Basin 059

NOTICE OF INTENT NO. ~~81236~~ 31236

1. OWNER Charlie & Rogene Hill
MAILING ADDRESS 1777 State Hwy. 806
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION JACKIE SUTHERS
2400 East St.

2. LOCATION SW 1/4 NW 1/4 Sec. 11 T 31N N/S R 45E E Lander County
PERMIT NO. (Issued by Water Resources) 11-420-15 (Parcel No.) Lot #2 (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	11	11
Sand & gravel		11	43	32
Clay		43	63	20
Clay w/gravel layers		63	80	17
Gray clay		80	82	2

RECEIVED 97 JUL 31 AM 10:18 STATE ENGINEER

Date started 11/3/96, 19__
Date completed 11/3/96, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		2.5 hrs.

8. WELL CONSTRUCTION
Depth Drilled 82 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10	Inches	0	Feet	82	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	80

Perforations:
Type perforation Mill slot
Size perforation 1/8 x 3
From 60 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 82 feet

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality Good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562

Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 7-30-97

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 64988
Permit No.
Basin 059

NOTICE OF INTENT NO. ~~31237~~ 31236

1. OWNER Charlie & Rogene Hill
MAILING ADDRESS 1777 State Hwy. 806
Battle Mountain, NV 89820

ADDRESS AT WELL LOCATION Jackie Suthers
2400 East St.
Battle Mountain, NV 89820

2. LOCATION SW ¼ NW ¼ Sec. 11 T. 31 (N) S R. 45 E. Lander County
PERMIT NO. (Issued by Water Resources) Parcel No. 011-420-~~14~~15 Subdivision Name Lot #2

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	11	11
Sand & gravel		11	43	32
Clay		43	63	20
Clay w/gravel layers		63	80	17
Gray clay		80	82	2

Date started 11/3, 1996
Date completed 11/3, 1996

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
12		2 1/2

8. WELL CONSTRUCTION
Depth Drilled 82 Feet Depth Cased 80 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
10	0	82

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	80

Perforations:
Type perforation Mill Slot
Size perforation 1/8 X 3
From 60 feet to 80 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 82 feet

9. WATER LEVEL
Static water level 12 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co. Inc. (Contractor)
Address 4675 W. Winnemucca Blvd. (Contractor)
Winnemucca, NV 89445
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562
Signed (By driller performing actual drilling on site or contractor)
Date 11-12-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627