WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65088
Permit No.
Basin 101
NOTICE OF INTENT NO. 32929

1. OWNER Lois Scoville
MAILING ADDRESS P.O. Box 418
Silver Springs, NV. 89529

ADDRESS AT WELL LOCATION
2090 Fox Rd.
Silver Springs, NV. 89529

2. LOCATION NW ¼ SW ¼ Sec. 29 T 17 N/S R 25 E Lyon County

PERMIT NO. (Issued by Water Resources) 17-552-02 (Parcel No.) Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand & Gravel		0	4	4
Hard Packed Clay		4	12	8
Soft Clay		12	19	7
Coarse Sand		19	24	5
Soft Clay		24	34	10
Clay & Sand		34	40	6
SAnd & Coarse Gravel		40	45	5
Sand		45	58	13
Sand & Gravel		58	60	2
Sand & Big Gravel		60	70	10
Black & Gray Clay		70	76	6
Sand & Gravel		76	88	12
Sandy Clay		88	125	37
Fine Sand		125	150	25
Coarse Sand		150	153	3
Coarse Sand & Gravel	X	153	161	8

Date started October 5, 1995
Date completed October 6, 1995

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 161 Feet Depth Cased 161 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
8-1/2 Inches	0 Feet	161 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6-5/8	12.92	.188	0	161

Perforations:
Type perforation Mill Cut
Size perforation 1/8"
From 153 feet to 161 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50ft.
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 161 feet

9. WATER LEVEL
Static water level 49' 1" feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature Cool °F Quality Unknown

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name PARSONS DRILLING, INC. (Contractor)
Address P.O. BOX 1265 (Contractor)
FALLON, NV. 89407-1265
Nevada contractor's license number issued by the State Contractor's Board 29064
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1758
Signed (By driller performing actual drilling on site or contractor)
Date 11/8/95

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627