

WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. **65399**
 Rec. _____
 Well No. _____
 Permit No. _____
Do not fill in

Owner Crystal Springs Ranch Driller Patrick H. Thompson

Address Alamo, Nevada Address 3215 Cinder Lane. L.V. Lic. No. 192

Location of well: SW of NW SE 24 1/4 Sec. 8, T. 3 N/S, R. 60 E, in Lincoln County
 or West of Road N. of #13041

Water will be used for Irrigation Total depth of well 590'

Size of drilled hole 14" Weight of casing per linear foot 45.68#

Thickness of casing .250 Temp. of water cool

Diameter and length of casing Diameter - 14" Length - 550'
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure.....

If nonflowing well give depth of standing water from surface 195'

If flowing well describe control works.....
 (Type and size of valve, etc.)

Date of commencement of well 9-30-65 Date of completion of well 10-28-65

Type of well rig Cable Tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	40	40	Sand gravel - small boulders
40	70	30	Loose gravel - small boulders
70	100	30	Sand gravel-small boulders
100	410	310	Sand Gravel
410	435	25	Sand gravel - fairly loose
435	485	50	Loose sand, gravel
485	590	105	Sand gravel

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 195' to 590' ft.

Other aquifers.....

First water at 195' feet.

Casing perforated

from 195' to 550' ft.

Size of perforations

3/8 x 3, 8 rows around



