WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

FINALIZED MH

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 63756
Permit No.
Basin 071

NOTICE OF INTENT NO. 28354

1. OWNER Gregg & Jodi Kraft
MAILING ADDRESS 9405 Grass Valley Rd.
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
9405 Grass Valley Rd. (3050 Potbelly Road)
Winnemucca, NV 89445

2. LOCATION SW 1/4 NE 1/4 Sec. 25 T 35N N/S R 37 E Humboldt County
PERMIT NO. Issued by Water Resources | 14-143-22 Parcel No. | Parcel A Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Clay		0	5	5
Sand & gravel		5	36	31
Clay		36	89	53
Sand & gravel		89	155	66

RECEIVED 97 MAR 19 AM 11:26 STATE ENGINEER'S OFFICE

See Deepening Log #110400
40.882,850°N NAD27 D.D.
117.761,767°W

Date started 3/17/97 , 19__
Date completed 3/17/97 , 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
30		2

8. WELL CONSTRUCTION
Depth Drilled 155 Feet Depth Cased 150 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 7/8	Inches	0	Feet	155	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	150

Perforations:
Type perforation Single row mill slot
Size perforation 1/8 X 3
From 130 feet to 150 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 155 feet

9. WATER LEVEL
Static water level 100 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2019

Signed Jeri Q. Tompk
By driller performing actual drilling on-site or contractor

Date 3-18-97