WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65769
Permit No.
Basin 071

NOTICE OF INTENT NO. 35844

1. OWNER Richard Brown
MAILING ADDRESS 3565 Brown Ln.
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION
Corner of Davey & Brayton Rd.
Winnemucca, NV 89445

2. LOCATION SW 1/4 SE 1/4 Sec. 7 T 35N N/S R 38 E Humbodt County
PERMIT NO. (Issued by Water Resources) Parcel No. 10-482-18 Subdivision Name Lot 8AC

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	5	5
Cobbles		5	95	90
Fractured Granite		95	110	15
Basalt		110	135	25
Cobbles		135	149	14
Basalt		149	173	24
Sand & gravel		173	190	17

97 MAR 16 AM 11:06
STATE ENGINEER

Date started 3/4/97, 19__
Date completed 3/7/97, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [X] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
15		2

8. WELL CONSTRUCTION
Depth Drilled 190 Feet Depth Cased 180 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 7/8	Inches	0	Feet	100	Feet
6 1/8	Inches	100	Feet	190	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	+1	100
5 9/16		.188	90	180

Perforations:
Type perforation Single row mill slot
Size perforation 1/8 X 3
From 160 feet to 180 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [ ] Yes [X] No
From feet to feet

9. WATER LEVEL
Static water level 140 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2019

Signed [signature] (By driller performing actual drilling on-site or contractor)
Date 3-15-97