WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65813
Permit No.
Basin 212

NOTICE OF INTENT NO. 11165

1. OWNER South Land Corporation
MAILING ADDRESS c/o Converse Consultants 4670 S. Polaris Ave., Las Vegas
ADDRESS AT WELL LOCATION 4890 N. TROPICANA AVE LAS VEGAS NV

2. LOCATION SE ¼ SW ¼ Sec. 19 T. 21 N/S R. 61 E. CLARK County
PERMIT NO. MO-2164 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☒ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
ASPHALT + FILL		0	3	3
Clayey silt w/gravel		3	9	6
Silty clay		9	13	4
Clayey silt		13	14.5	1.5
Clay w/silt		14.5	19	4.5
Silty clay		19	22	3
Silt w/clay		22	23.5	1.5
Caliche		23.5	25	1.5
Clayey silt		25	28	3.0
Silt w/clays		28	29.5	1.5
Clay w/silts		29.5	33.5	4
Gravelly sand w/silt		33.5	40	6.5
Clay w/silt gravels		40	53.5	13.5
T.D = 53.5'				

Date started July 17, 1992
Date completed July 17, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

RECEIVED
AUG 13 1992
Div. of Water Resources
Branch Office - Las Vegas, NV

8. WELL CONSTRUCTION
Depth Drilled 53.5 Feet Depth Cased 53.5 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	53.5 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	07	SCH. 40	0	53.5

Perforations:
Type perforation Factory Slotted
Size perforation 0.020
From 33.5 feet to 53.5 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 28
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 30 feet to 53.5 feet

9. WATER LEVEL
Static water level ~ 40' feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Richard Leblanc / Converse Consultants (Contractor)
Address 4670 S. Polaris AVE (Contractor)
LAS VEGAS NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1817
Signed (By driller performing actual drilling on site or contractor)
Date 8.13.92

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627