WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65815
Permit No.
Basin 212

NOTICE OF INTENT NO. 9638

1. OWNER CLARK County School Dist.
MAILING ADDRESS 1700 Galleria Bldg C.
Henderson NV 89014

ADDRESS AT WELL LOCATION R.C. White Trans. Ctr.
4499 S. ARVILLE ST.
LAS VEGAS NV.

2. LOCATION SE ¼ NW ¼ Sec. 19 T. 21 N/S R. 61 E. CLARK County
PERMIT NO. MO-2147 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☑ Air ☐ Other

6. LITHOLOGIC LOG MW-7

Material	Water Strata	From	To	Thickness
Asphaltic Concrete		0	3"	3"
SILTY SAND		3"	4'	3'9"
CLAYEY SAND		4'	14'	10'
GRAVELLY SAND		14'	17'	3'
SILTY SAND		17'	22'	5'
CLAYEY SAND	☑	22'	26'	4'
SANDY CLAY		26'	32'	6'
CALICHE		32'	34½	2.5'
SANDY CLAY		34½	41½	6.5'
SILTY CLAY		41½	50	9'
	TD - 50½			

RECEIVED
OCT 19 1992
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started 8-31-92, 19
Date completed 9-1, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 50' Feet Depth Cased 45' Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2-INCH		SCH 40	0	45

Perforations:
Type perforation MACHINE slotted
Size perforation 0.020
From 15 feet to 45' feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 11 (2' Bentonite)
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☑ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 13 feet to 50 feet

9. WATER LEVEL
Static water level 24 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name DON WILSON
Address 4670 S. Polaris Ave. Contractor
LAS VEGAS, NV Contractor
Nevada contractor's license number issued by the State Contractor's Board.
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1589
Signed [signature] By driller performing actual drilling on site or contractor
Date 10-2-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627