WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65869
Permit No.
Basin 212

NOTICE OF INTENT NO. 9625

1. OWNER MGM GRAND HOTEL
MAILING ADDRESS c/o Converse Consultants 4670 S. Polaris Ave., Las Vegas
ADDRESS AT WELL LOCATION MGM GRAND HOTEL Corner of Strip & Las Vegas Blvd. Las Vegas, Nevada

2. LOCATION NW ¼ SW ¼ Sec. 21 T. 21 N(S) R. 61 E. Clark County
PERMIT NO. MO-2145 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☑ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	.5	.5
Type II Base		.5	2	1.5
Sandy silt				
tr. clay / Tr. gravel		2	7	5'
Silty fine sand				
Tr. gravel		7	12	5
gravelly sand		12	14	2'
Caliche		14	18	4'
Silty sand				
w/ gravel		18	29	11'
Caliche		29	34	5'
Sandy clay				
tr. gravel		34	45	11'
T.D. =	45'			

RECEIVED
AUG 26 1992
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started 6-18, 1992
Date completed 6-19, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 45 Feet Depth Cased 45 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
Air R.	5 3/4" Inches	0 Feet	30 Feet
HSA.	8" Inches	0 Feet	45 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	.71 lbs	SCH. 40	0	45

Perforations:
Type perforation factory slotted
Size perforation 0.020
From 15 feet to 45 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-13 / 11-13' Bent.
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 13 feet to 45 feet

9. WATER LEVEL
Static water level 27.7 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Richard LeBlanc (Contractor)
Address 4670 S. Polaris Ave. Las Vegas NV. 89103 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1817
Signed R. LeBlanc (By driller performing actual drilling on site or contractor)
Date 8-17-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627