


WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA  
DIVISION OF WATER RESOURCES

OFFICE USE ONLY



Log No. 65928  
Permit No. 061  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36028

1. OWNER BARRICK GOLDSTRIKE ADDRESS AT WELL LOCATION BARRICK GOLDSTRIKE MINE  
MAILING ADDRESS P.O. BOX 29 ELKO, NV 89801

2. LOCATION SW 1/4 NE 1/4 Sec 19 T. 36 N S R. 50 E EUREKA County  
PERMIT NO. 58355 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED:  New Well,  Replace,  Recondition,  Deepen,  Abandon,  Other  
4. PROPOSED USE:  Domestic,  Municipal/Industrial,  Irrigation,  Monitor,  Test,  Stock  
5. WELL TYPE:  Cable,  Rotary,  RVC,  Air,  Other

6. LITHOLOGIC LOG table with columns: Material, Water Strata, From, To, Thickness. Rows include CLAYS, SAND, GRAVEL, CARLIN FORMATION, BROWN CLAYS WITH BROWN AND GRAY ROCK, BLACK, GRAY & BROWN ROCK, GRAY CLAY WITH ROCK, GRAY & BROWN ROCK WITH LITTLE RED, BLACK & BROWN ROCK, BROWN & RED ROCK, GRAY ROCK, SOME BROWN, BROWN, BLACK & GRAY ROCK.

8. WELL CONSTRUCTION: Depth Drilled 810 Feet, Depth Cased 800 Feet  
HOLE DIAMETER (BIT SIZE) table with columns: From, To, Inches, Feet. Rows: 17-1/2 Inches (0-20 Feet), 9-7/8 Inches (20-810 Feet)

CASING SCHEDULE table with columns: Size O.D. (Inches), Weight/Ft. (Pounds), Wall Thickness (Inches), From (Feet), To (Feet). Rows: 12-1/2 (49.5, .375, 0-20), 6-5/8 (17.02, .250, +2-118)

Perforations: Type perforation LOUVERED, Size perforation .125  
From 800 SCREEN feet to 118 SCREEN feet

Surface Seal:  Yes,  No. Seal Type:  Neat Cement,  Cement Grout,  Concrete Grout  
Depth of Seal 104  
Placement Method:  Pumped,  Poured  
Gravel Packed:  Yes,  No. From 810 feet to 104 feet

9. WATER LEVEL: Static water level 151.1 feet below land surface, Artesian flow NO, G.P.M. P.S.I., Water temperature °F, Quality

Date started MARCH 9, 19.97  
Date completed MARCH 15, 19.97

7. WELL TEST DATA table with columns: TEST METHOD (Bailer, Pump, Air Lift), G.P.M., Draw Down (Feet Below Static), Time (Hours). Rows: STATIC (151.1), 50 GPM (15 MIN), 25 GPM (30 MIN), 23 GPM (45 MIN), 22 GPM (1 HR), DRAWDOWN (510), RECOVERED (190, 1 HR)

10. DRILLER'S CERTIFICATION: This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name LANG EXPLORATORY DRILLING Contractor  
Address 2286 WEST 1500 SOUTH Contractor SALT LAKE CITY, UTAH 84104  
Nevada contractor's license number issued by the State Contractor's Board 0021976  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2039  
Signed DENNY ROBBLEE By driller performing actual drilling on site or contractor  
Date 2-22-97