PPW-6

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 65934
Permit No.
Basin 061

NOTICE OF INTENT NO. 13924

1. OWNER BARRICK GOLDSTRIKE
MAILING ADDRESS P.O. BOX 29
ELKO, NV 89801

ADDRESS AT WELL LOCATION
BARRICK GOLDSTRIKE MINE

2. LOCATION SW ¼ NE ¼ Sec 19 T 36 N/S R 50 E EUREKA County
PERMIT NO. 52061; W-275 (Issued by Water Resources) N/A (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
☐ New Well ☐ Replace ☐ Recondition
☐ Deepen ☒ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic mining ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP 900 FT OF WELL WAS MINED OFF. DISPLACED BENTONITE SLURRY WITH 70 SECOND FUNNEL VISCOSITY FROM 1300 FT TO 950 FT. DISPLACED 16 LB/GAL CEMENT SLURRY FROM 950 FT TO 900 FT (SURFACE)				

Plugging of Log #52106

Date started FEBRUARY 18, 19 97
Date completed FEBRUARY 18, 19 97

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1300 Feet Depth Cased 1300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
27 Inches	0 Feet	20 Feet
20-1/2 Inches	20 Feet	1300 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	86.61	.375	0	20
14	36.71	.250	0	770
14	36.71	.250	950	997
14	36.71	.250	1270	1300

Perforations:
Type perforation LOUVERED
Size perforation .125 X 2.5
From 770 feet to 950 feet
From 997 feet to 1270 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 1300 feet

9. WATER LEVEL
Static water level 328 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1716

Signed DAVID HAAS David Haas
By driller performing actual drilling on site or contractor

Date FEBRUARY 28, 1997

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627