

OFFICE USE ONLY
 Log No. 66019
 Permit 084
 Basin 084

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 33891

1. OWNER STANLEY LIVINGSTON HOKE ADDRESS AT WELL LOCATION 2600 Whiskey Springs Road
 MAILING ADDRESS 836 Saltwind Drive St. Helena Island, S.C. 29920 Reno, Nevada 89510 Rocketry Area
 2. LOCATION NW 1/4 NE 1/4 Sec 7 T 22N N/S R 22 E Washoe County
 PERMIT NO. 077-320-0499 Palomino Valley Area D Unit 11 7.2-2-2
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	2	2
Red clay		2	5	3
Brown sandy clay		5	21	16
Dark black clay		21	27	6
Brown sandy clay		27	42	15
Reddish brown volcanic rock		42	57	15
Red volcanic rock		57	78	21
Brown volcanic rock		78	80	2
Purple volcanic rock		80	109	29
Green volcanic rock		109	170	61
Purple volcanic rock		170	179	9
Brown volcanic rock		179	345	166
Brown green mix volcanic rock		345	410	65
Soft zone (NO WATER)		410	412	2
Brown green mix volcanic rock		412	428	16
Green volcanic rock		428	458	30
Gray volcanic rock		458	471	13
Brown volcanic rock		471	527	56
Fracture brown volcanic rock (app 15 GPM)	X	527	537	10
Brown volcanic rock		537	640	103
Fracture brown volcanic rock	X	640	685	15
Brown volcanic rock		685	700	15

8. WELL CONSTRUCTION
 Depth Drilled 700 Feet Depth Cased 700 Feet

HOLE DIAMETER (BIT SIZE)
 From To
10 Inches 0 Feet 50 Feet
8 5/8 Inches 50 Feet 700 Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>6 5/8</u>		<u>.188</u>	<u>0</u>	<u>700</u>

Perforations:
 Type perforation factory sawed slot
 Size perforation 3/32 x 3 x 5 around
 From 534 feet to 554 feet
 From 634 feet to 694 feet
 From feet to feet
 From feet to feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 50 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout

Gravel Packed: Yes No
 From 50 feet to 700 feet

9. WATER LEVEL
 Static water level: 495 feet below land surface
 Artesian flow G.P.M. 42 P.S.I.
 Water temperature cold °F Quality clear

Date started 4-16-97, 19
 Date completed 4-20-97, 19

7. WELL TEST DATA

TEST METHOD:	G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift	<u>42</u>		
		<u>google estimate: 39.794283°N</u>	
		<u>119.352060°W</u>	
<u>*recor. by well log # 112820</u>			

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. Contractor
 Address P.O. BOX 12370 Contractor
RENO, NEVADA 89510

Nevada contractor's license number 0022549
 issued by the State Contractor's Board

Nevada driller's license number issued by the 923
 Division of Water Resources the on-site driller:

Signed [Signature]
 by driller performing actual drilling on site or contractor

Date April 22, 1997

