MW-01

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 67375
Permit No.
Basin 082

NOTICE OF INTENT NO. 25575

1. OWNER ALTA GOLD COMPANY
MAILING ADDRESS 601 WHITNEY RANCH DR #10
HENDERSON, NV 89014

ADDRESS AT WELL LOCATION
OLINGHOUSE MINE SITE

2. LOCATION SW ¼ SE ¼ Sec. 20 T 21 (N) S R 23 E WASHOE County
PERMIT NO. M/O 1093 (Issued by Water Resources) NA/ (Parcel No.) N/A (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [X] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
TOP SOIL		0	15	15
GREY ROCK-CLAY		15	50	35
GREY ROCK CLAY		50	155	105
BROKEN BLACK ROCK W/ GREY		155	180	25
GREY ROCK - CLAY		180	355	175
BROKEN GREY ROCK	X	355	390	35
GREY ROCK		390	455	65
BLACK ROCK W/ CLAY		455	470	15
SMALL FRACTURED ROCK	X	470	495	25
GREY ROCK		495	525	30

Date started 11-6-96, 19
Date completed 11-10-96, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 525 Feet Depth Cased 515 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
14-3/4 Inches	0 Feet	17 Feet	
10 Inches	17 Feet	525 Feet	
Inches	Feet	Feet	

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10-1/2	28.04	.250	0	20
5-1/2	3.91	SCH 80	+2	465

Perforations:
Type perforation SLOT
Size perforation .020
From 465 feet to 515 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 130
Placement Method: [X] Pumped [ ] Poured
130-450 BENTONITE HOLE PLUG
Gravel Packed: [X] Yes [ ] No
From 450 feet to 525 feet

Seal Type:
[X] Neat Cement
[ ] Cement Grout
[ ] Concrete Grout

9. WATER LEVEL
Static water level 397 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature COOL °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 WEST 1500 SOUTH (Contractor)
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number issued by the State Contractor's Board 0021976

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1995

Signed GUADALUPE JACOBO (By driller performing actual drilling on site or contractor)
Date 11-10-96

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627