

WHITE-DIVISION OF WATER RESOURCES
CANARY-CLIENT'S COPY
PINK-WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY
Log No. 67385
Permit No. 51772
Basin 03

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 9717

1. OWNER AMAX SLEEPER MINE ADDRESS AT WELL LOCATION AMAX SLEEPER MINE
 MAILING ADDRESS 600 SOD HOUSE ROAD
WINNEMUCCA, NV 89445

2. LOCATION NE 1/4 NW 1/4 Sec. 21 T 40 S R 35 E HUMBOLDT County
 PERMIT NO. MM-54/51772 N/A
 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other

4. PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
MIX & PUMP ABANDONITE SLURRY		FROM		
BOTTOM OF WELL UP TO 62'				
HOLE PLUG				
UP TO 50' THEM CEMENT UP TO SURFACE				
6800 GALLONS OF ABANDONITE SLURRY				
800 GALLONS OF CEMENT				
*NOTE: 72' HAS BEEN CUT OFF TO P OF WELL TOTAL DEPTH NOW IS 728 GRAVEL DROPPED IN HOLE HAD TO HOLE PLUG & CEMENT BETWEEN HOLE AND CASING.				

Plugging of Log # 29887

RECEIVED
STATE ENGINEER
DIVISION OF WATER RESOURCES
SEP 11 AM 8:15

8. WELL CONSTRUCTION
 Depth Drilled 600 Feet Depth Cased 600 Feet

HOLE DIAMETER (BIT SIZE)
 From 22 Inches To 0 Feet 600 Feet
 Inches Feet Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	1/8	1	600

Perforations:
 Type perforation 16" JOHNSON HI-CAP WELL SCREEN
 Size perforation MILLED 3"X1/8"
 From PERF 30' feet to 120 feet
 From SCREEN 120 feet to 600 feet
 From _____ feet to _____ feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Neat Cement
 Cement Grout
 Concrete Grout

Depth of Seal WAS 50 BUT WELL WAS CUT DOWN

Placement Method: Pumped Poured
 BUT IT DROPPED CEMENT OUTSIDE OF CASING

Gravel Packed: Yes No
 From 600 feet to 50 feet

9. WATER LEVEL
 Static water level N/A feet below land surface
 Artesian flow N/A G.P.M. N/A P.S.I.
 Water temperature _____ °F Quality _____

Date started 8-12-96, 19_____
 Date completed 8-13-96, 19_____

7. WELL TEST DATA

TEST METHOD: Bailer Pump Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING Contractor
 Address 2286 WEST 1500 SOUTH Contractor
SALT LAKE CITY, UTAH 84104

Nevada contractor's license number 0021976
 issued by the State Contractor's Board

Nevada driller's license number issued by the 1948
 Division of Water Resources, the on-site driller

Signed DARYL GLANZMAN *Daryl Glanzman*
 By driller performing actual drilling on site or contractor

Date 8-13-96