WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 673886
Permit No.
Basin 094

NOTICE OF INTENT NO. 30615

1. OWNER DAVE GASKILL
MAILING ADDRESS 755 Kuenzli Street #104
Reno, Nevada 89502

ADDRESS AT WELL LOCATION
15095 Red Rock Road
REno, Nevada 89506

2. LOCATION SE ¼ NW ¼ Sec. 7 T. 22N N/S R. 19 E. Washoe County
PERMIT NO. (Issued by Water Resources) 079-382-59 (Parcel No.) Red Rock Estates #8 parcel 1 (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	11	10
Gray sand		11	13	2
Brown sandy clay		13	51	38
Soft zone (NO WATER)		51	52	1
Brown sandy clay, some gravels		52	88	36
Gray sand		88	89	1
Brown sandy clays		89	221	132
Soft zone (app ½ GPM)	X	221	222	1
Brown sandy clays		222	254	32
Soft zone (app 10 GPM)	X	254	261	7
Brown clays with decom--posed granite mixed		261	284	23
Soft zone	X	284	286	2
Brown clays with decom--posed granite mixed		286	300	14

Date started 3-31-97, 19
Date completed 4-1-97, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
14		

8. WELL CONSTRUCTION
Depth Drilled 300 Feet Depth Cased 300 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	300 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	300

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 245 feet to 265 feet
From 275 feet to 295 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 300 feet

9. WATER LEVEL
Static water level 105 feet below land surface
Artesian flow G.P.M. 14 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed [signature]
By driller performing actual drilling on site or contractor
Date April 3, 1997

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627