WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68118
Permit No.
Basin 071

NOTICE OF INTENT NO 33489

1. OWNER Rich Brown
MAILING ADDRESS 3565 Brown Ln.
Winnemucca, NV 89445

ADDRESS AT WELL LOCATION For McMillon
4710 Brayton
Winnemucca, NV 89445

2. LOCATION SW ¼ SE ¼ Sec 7 T 35 (N)/S R 38 E Humboldt County

PERMIT NO. Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Sand & Sandy Clay | | 0 | 5 | 5 |
| Hard sand | | 5 | 9 | 4 |
| Gravel | | 9 | 18 | 9 |
| Clay w/gravel/cobbles | | 18 | 70 | 52 |
| Rock w/clay fractures | | 70 | 135 | 55 |
| Clay | | 135 | 145 | 10 |
| Rock w/clay fractures | | 145 | 190 | 55 |
| Rock w/sand & gravel | | 190 | 227 | 37 |

Date started 8/5, 19 96
Date completed 8/9, 19 96

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

| | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|---|
| Air lift | 25 | | 3 1/2 |

8. WELL CONSTRUCTION
Depth Drilled 227 Feet Depth Cased 220 Feet

HOLE DIAMETER (BIT SIZE)

| | From | To |
|---|---|---|
| 9 7/8 Inches | 0 Feet | 227 Feet |
| Inches | Feet | Feet |
| Inches | Feet | Feet |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6 5/8 | | 1/4" | +1 | 220 |

Perforations:
Type perforation Mill slot
Size perforation 1/8" X 3
From 180 feet to 220 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [X] Pumped [ ] Poured

Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 227 feet

9. WATER LEVEL
Static water level 160 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humboldt Drilling & Pump Co. Inc. (Contractor)
Address 4675 W. Winnemucca Blvd. (Contractor)
Winnemucca, NV 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1562

Signed [signature]
By driller performing actual drilling on site or contractor

Date 8/22/96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627