WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68139
Permit No.
Basin 51

NOTICE OF INTENT NO. 34021

1. OWNER Newmont Gold Co.
MAILING ADDRESS P.O. Box 669 Carlin Nev. 89822
ADDRESS AT WELL LOCATION Newmont Gold North Area Pete Orco Body

2. LOCATION NW ¼ ~~BB~~ NW ¼ Sec. 19 T. 35 N/S R. 51 E. Eureka County
PERMIT NO. MO 1091 A (Issued by Water Resources) | Parcel No. | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand Gravel	Dry	0	20	20
Black Rock	Dry	20	240	220
Black Rock Water	40gpm	240	280	20
Black & Gray Rock	Dry	280	400	120

RECEIVED
97 AUG 20 AM 11:14
STATE ENGINEERS OFFICE

Date started 8-3, 1997
Date completed 8-7, 1997

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
40 to 50	360	4 hrs

8. WELL CONSTRUCTION
Depth Drilled 400 Feet Depth Cased 400 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
11 7/8 Inches	0 Feet	20 Feet
6 1/2 Inches	20 Feet	240 Feet
6 1/4 Inches	240 Feet	400 Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
7	19	6.065	+2	20
2 3/8	1.45	0.276 PVC	+2	378'

Perforations:
Type perforation PVC slotted screen
Size perforation HORIZONTAL .20 SLOT
From 358 feet to 378 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 60
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 337 feet to 380' feet

9. WATER LEVEL
Static water level 60 feet below land surface
Artesian flow 40 to 50 G.P.M. P.S.I.
Water temperature 54 °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name O'Keefe Drilling (Contractor)
Address Box 3810 Butte Mt. 58702 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board C-23-0030581
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1703
Signed Frank Crink
By driller performing actual drilling on site or contractor
Date 8-17-97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627