WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68274
Permit No.
Basin 063

NOTICE OF INTENT NO. 36338

1. OWNER MIDAS JOINT VENTURE
MAILING ADDRESS 6151 LAKESIDE DRIVE SUITE 2100
RENO, NV 89511

ADDRESS AT WELL LOCATION
KEN SNYDER MINE NEAR MIDAS, NEVADA

2. LOCATION NW 1/4 NW 1/4 Sec. 27 T 39N N/S R 46E E ELKO County
PERMIT NO. M/O 1034 (Issued by Water Resources) | MW12 (Parcel No.) | TRACT OF LAND (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [X] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [ ] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
CLAY AND SILTSTONE		0	65	65
ALTERED CLAY AND SILTSTONE		65	135	70
BROWN SILTSTONE		135	160	25
GREY SILTSTONE	X	160	210	50
GREY AND BLACK BASALT	X	210	235	25
GREY SILTSTONE		235	280	45

Placed 3/8 bentonite seal from 83' to 70'.

Pumped abandonite from 70' to 10'

Date started 5/7/97, 19__
Date completed 5/8/97, 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
1.5		1.5

8. WELL CONSTRUCTION
Depth Drilled 280 Feet Depth Cased 280 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6.5"	Inches	0 Feet	280 Feet
	Inches	Feet	Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.5"	PVC	SCH 40	+.5	280

Perforations:
Type perforation SCREEN
Size perforation .050 SLOT
From 100 feet to 260 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 10'
Placement Method: [ ] Pumped [X] Poured
Seal Type: [X] Neat Cement [ ] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 83 feet to 280 feet

9. WATER LEVEL
Static water level 109 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Hackworth Drilling, Inc. (Contractor)
Address P.O. Box 850 (Contractor)
Elko, NV 89803

Nevada contractor's license number issued by the State Contractor's Board 020582

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1654

Signed
By driller performing actual drilling on-site or contractor
Date 6-13-97