WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68420
Permit No.
Basin 077

NOTICE OF INTENT NO. 28343

1. OWNER Valerie Allred
MAILING ADDRESS P.O. Box 1795
Winnemucca, NV 89446

ADDRESS AT WELL LOCATION corner of Bishop & Phyllis Lane
Golconda, NV 89414

2. LOCATION SE ¼ SW ¼ Sec. 31 T 36 N/S R 40 E Humbolt County

PERMIT NO. (Issued by Water Resources) Parcel No. D-2 Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
sand & gravel		0	45	45
clay		45	55	10
large sand & gravel		55	92	37
bedrock w/ fractures		92	250	158

Date started March 23, 1996, 19
Date completed March 25, 1996, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		3

8. WELL CONSTRUCTION
Depth Drilled 250 Feet Depth Cased 250 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	250 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
65/8		.188	+1	250

Perforations:
Type perforation single row mill slot
Size perforation 178 x 2
From 250 feet to 230 feet
From 210 feet to 170 feet
From 150 feet to 110 feet
From 90 feet to 70 feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100
Placement Method: [X] Pumped [ ] Poured

Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 250 feet to 100 feet

9. WATER LEVEL
Static water level 80 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Humbolt Drilling & pump Co., Inc. (Contractor)
Address 4675 W. Winnemucca Blvd. 109-13 (Contractor)
Winnemucca, nv 89445

Nevada contractor's license number issued by the State Contractor's Board 015234

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1154T-1

Signed [signature] (By driller performing actual drilling on site or contractor)
Date 4-15-96

(Rev. 3-91)

USE ADDITIONAL SHEETS IF NECESSARY

(O)-627