WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68721
Permit No.
Basin 212

NOTICE OF INTENT NO. 12150

1. OWNER LAS VEGAS VALLEY WATER DIST
MAILING ADDRESS 3700 W. CHARLESTON BLVD LAS VEGAS NV 89153
ADDRESS AT WELL LOCATION DELL H. ROBISON JHS, 825 MARION DRIVE, LAS VEGAS, NV

2. LOCATION NW ¼ SE ¼ Sec. 29 T. 20 N/S R. 62 E. CLARK County
PERMIT NO. M0-2384 (Issued by Water Resources) | 020-190-002 (Parcel No.) | Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other AUGER

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
SANDY CLAY		0	2	2
SILTY SAND		2	3	1
SILTY CLAY		3	5	2
LEAN CLAY		5	7	2
SILTY SAND		7	12	5
GRAVELLY SAND		12	14	2
SILTY SAND		14	15	1
CLAYEY SAND		15	16	1
SANDY LEAN CLAY		16	19	3
SILTY SAND		19	26	7
SANDY SILT		26	32	6
SANDY GRAVEL	X	32	37	5
WELL GRADED SAND		37	41	4
SANDY GRAVEL		41	44	3
POORLY GRADED SAND		44	46	2
SANDY GRAVEL		46	48	2
WELL GRADED SAND		48	52	4
SANDY CLAY		52	53.5	1.5
GRAVELLY SAND		53.5	59	5.5
CLAY		59	61	2

RECEIVED
JAN 21 1994
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started JAN 17, 19 94
Date completed JAN 17, 19 94

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 61 Feet Depth Cased 60 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From Feet	To Feet
8	0	61

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.5	1.4	0.216	0	60

Perforations:
Type perforation FACTORY SLOT
Size perforation 0.020
From 40 feet to 60 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-36'/36-38' BENTONITE
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 38 feet to 61 feet

9. WATER LEVEL
Static water level 24 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name THOMAS HIGH (Contractor)
Address 4670 SO POLARIS AVE (Contractor)
LAS VEGAS NV 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1869
Signed (By driller performing actual drilling on site or contractor)
Date JAN 18, 1994

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 3-91) (O)-627