WHITE - DIVISION OF WATER RESOURCES
CANARY - CLIENT'S COPY
PINK - WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68774
Permit No.
Basin 162

NOTICE OF INTENT NO. 15560

1. OWNER Sundance Homes
MAILING ADDRESS 241 E. Calvary
Pahrump, NV 89048

ADDRESS AT WELL LOCATION
241 E. Calvary

2. LOCATION NE 1/4 NE 1/4 Sec. 34 T 20 N/S R 53E E NYE County
PERMIT NO. Issued by Water Resources
40-662-09 Parcel No.
Calvada Valley Subdivision Name

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BROWN CLAY		0	8	8
GREY CALACHE		8	11	3
BROWN CALACHE		11	15	4
GREY CALACHE		15	18	3
BROWN CLAY		18	29	11
BROWN CLAY		29	37	8
LIGHT BROWN CLAY		37	46	9
BROWN CLAY/GRAVEL		46	58	12
BROWN CLAY		58	65	7
BROWN CLAY/GRAVEL	X	65	78	13
LIGHT BROWN CLAY	X	78	87	9
BROWN CLAY	X	87	99	12
BROWN CLAY	X	99	118	19
LIGHT BROWN CLAY/ GRAVEL	X	118	129	11
LIGHT BROWN CLAY	X	129	140	11

RECEIVED
OCT 30 1997
WATER RESOURCES
LAS VEGAS OFFICE

Date started 10/18/97 , 19__
Date completed 10/18/97 , 19__

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [X] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
.5	na	.50

8. WELL CONSTRUCTION
Depth Drilled 140 Feet Depth Cased 140 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12 7/8	Inches	0	Feet	140	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	3.7	.280	0	140

Perforations:
Type perforation SAW CUT
Size perforation .188
From 110 feet to 140 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 50
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [X] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 50 feet to 140 feet

9. WATER LEVEL
Static water level 65 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature COOL °F Quality GOOD

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Strickland Construction Co., Inc. (Contractor)
Address 2301 Winery Road, Suite 2 (Contractor)
Pahrump, NV 89048
Nevada contractor's license number issued by the State Contractor's Board 40277
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2086
Signed Larry Strickland (By driller performing actual drilling on-site or contractor)
Date 10-28-97