WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 68941
Permit No.
Basin 100

NOTICE OF INTENT NO. 38316

1. OWNER MARK BERTINI
MAILING ADDRESS 17705 Northridge Ave
Reno, Nevada 89506

ADDRESS AT WELL LOCATION 17705 Northridge Ave.
Reno, Nevada 89506

2. LOCATION SE ¼ SW ¼ Sec. 29 T 21N N/S R 18 E Washoe County
PERMIT NO. (Issued by Water Resources) 081-192-10 (Parcel No.) Cold Springs (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Brown sandy clay		1	6	5
Soft brown clay		6	11	5
Brown sandy clay with gravels		11	26	15
Brown sandy clays		26	78	52
Coarse sands	X	78	81	3
Brown sandy clay		81	89	8
Coarse sands	X	89	91	2
Brown sandy clay		91	104	13
Med to coarse sands with gravels	X	104	117	13
Brown sandy clay		117	125	8

Date started 8-4-97, 19
Date completed 8-5-97, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
25		

8. WELL CONSTRUCTION
Depth Drilled 125 Feet Depth Cased 125 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches		0 Feet	50 Feet
8 5/8 Inches		50 Feet	125 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8		.188	0	125

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 80 feet to 120 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 50 feet
Placement Method: ☐ Pumped ☒ Poured
Seal Type: ☐ Neat Cement ☒ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 50 feet to 125 feet

9. WATER LEVEL
Static water level 55 feet below land surface
Artesian flow G.P.M. 25 P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name WAYNE DRILLING, INC. (Contractor)
Address P.O. BOX 12370 (Contractor)
RENO, NEVADA 89510

Nevada contractor's license number issued by the State Contractor's Board 0022547

Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923

Signed (By driller performing actual drilling on site or contractor)

Date August 7, 1997

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627