WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 69017
Permit No.
Basin 212

NOTICE OF INTENT NO. 14772

1. OWNER Gersten Management Co.
MAILING ADDRESS 15760 Ventura Blvd
Encino, CA 91436

ADDRESS AT WELL LOCATION 1325 E Tropicana
Las Vegas NV

2. LOCATION NW ¼ NW ¼ Sec. 26 T. 21 N/S R. 61 E. Clark County
PERMIT NO. MO-2748 Issued by Water Resources | 162-26-101-004 Parcel No. | MDB+M ~~[illegible]~~ Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Asphalt		0	2"	2"
reddish brown Gravelly Sand		2"	2'	1'10"
light brown Sandy clay w/Gravel		2'	4'	2'
Caliche		4'	4'6"	6"
light brown Sandy clay w/Gravel		4'6"	6	1'6"
Caliche		6'	7'	1'
light brown Sandy Clay		7'	7'6"	6"
Caliche		7'6"	8'	6"
light brown Gravelly Clay		8'	10'	2'
Caliche		10'	10'6"	6"
light brown Gravelly clay		10'6"	13'	2'6"
Caliche		13'	14'	1'
~~reddish brown partially cemented clay w/Gravel~~		~~14'~~		
light brown Gravelly clay		14'	15'6"	1'6"
Caliche		15'6"	16'6"	1'
reddish brown partially cemented Gravelly clay		16'6"	20'	3'6"

Date started 12-21-, 1996
Date completed 12-21-, 1996

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 20 Feet Depth Cased 20 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8 Inches		0 Feet	20 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2¼		1/8	0	5

Perforations:
Type perforation ~~Saw Cut~~ Factory Slotted
Size perforation .020
From 5 feet to 20 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 3
Placement Method: ☐ Pumped ☒ Poured

Seal Type: ☐ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 3 feet to 20 feet

9. WATER LEVEL
Static water level 10.5 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Weber Drilling Services (Contractor)
Address 115 S. Weber Dr. Ste 1 (Contractor)
Chandler AZ 85226
Nevada contractor's license number issued by the State Contractor's Board 39528
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M2057
Signed [signature] (By driller performing actual drilling on site or contractor)
Date 1-25-97

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627