

WHITE—DIVISION OF WATER RESOURCES
 CANARY—CLIENT'S COPY
 PINK—WELL DRILLER'S COPY

STATE OF NEVADA
 DIVISION OF WATER RESOURCES


OFFICE USE ONLY
 Log No. 69022
 Permit No. _____
 Basin 4-66-KELLY CREEK

PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. _____



1. OWNER Firstmiss Gold / Getchell Mine ADDRESS AT WELL LOCATION _____
P.O.Box 220 Getchell Mine (Pit)
Golconda, Nevada

2. LOCATION SW 1/4 SW 1/4 Sec 33 T 39 N/S R 42 E Humboldt
 PERMIT NO. Certificate # 2758 - - - - -
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition
 Deepen Abandon Other _____

4. DE WATER PROPOSED USE
 Domestic Irrigation Test
 Municipal/Industrial Monitor Stock

5. WELL TYPE
 Cable Rotary RVC
 Air Other _____

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|--------------|--------------|------|-----|-----------|
| Basalt | | 0 | 15 | 15 |
| Granodiorite | | 15 | 35 | 20 |
| Basalt | | 35 | 45 | 10 |
| Granodiorite | | 45 | 60 | 15 |
| Basalt | | 60 | 140 | 80 |
| Granodiorite | | 140 | 145 | 5 |
| Basalt | | 145 | 155 | 10 |
| Granodiorite | | 155 | 180 | 25 |
| Basalt | X | 180 | 330 | 150 |
| Granodiorite | X | 330 | 420 | 90 |
| Basalt | X | 420 | 425 | 5 |
| Granodiorite | X | 425 | 430 | 5 |
| Basalt | X | 430 | 460 | 30 |
| " | X | 460 | 470 | 10 |
| " | X | 470 | 700 | 230 |

First Water at 290'
 Very hard formation

8. WELL CONSTRUCTION
 Depth Drilled 700 Feet Depth Cased 685 Feet

HOLE DIAMETER (BIT SIZE)
 From To
14 3/4 Inches 0 Feet 700 Feet
 _____ Inches _____ Feet _____ Feet
 _____ Inches _____ Feet _____ Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 10 3/4 | 28.04 | .250 | +2 | 185 |
| | | | | |
| | | | | |

Perforations: Triple Mill Slot
 Type perforation _____
 Size perforation 1/8 X 3
 From 185 feet to 685 feet
 From _____ feet to _____ feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 10 _____
 Neat Cement
 Placement Method: Pumped Concrete Grout
 Poured

Gravel Packed: Yes No
 From 10 feet to 700 feet

9. WATER LEVEL
 Static water level 220 feet below land surface
 Artesian flow _____ G.P.M. _____ P.S.I.
 Water temperature norm °F Quality good

Date started Sept. 22 1992
 Date completed Sept. 30 1992

7. WELL TEST DATA

| TEST METHOD: | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--|------------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift | <u>300</u> | <u>air on drill rig</u> | |
| | | | |
| | | | |
| | | | |
| | | | |

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Humboldt Drilling and Pump Co.
Contractor
 Address P.O.Box 590
Contractor
Winnemucca Nevada 89446-0590
 Nevada contractor's license number 015234
 issued by the State Contractor's Board.
 Nevada driller's license number issued by the 1713
 Division of Water Resources, the on-site driller.
 Signed _____
By driller performing actual drilling on site or contractor
 Date _____