WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 69115
Permit No.
Basin ~~212~~ 215

NOTICE OF INTENT NO. 11159

1. OWNER Burchette & Good
MAILING ADDRESS c/o Converse Consultants 4670 S. Polaris Ave, Las Vegas
ADDRESS AT WELL LOCATION Burchette & Good Calville Bay, Nevada
2. LOCATION NW ¼ SW ¼ Sec. 9 T. 21 N/S R. 65 E. Clark County
PERMIT NO. M02160 Issued by Water Resources | Parcel No. | Subdivision Name

3. WORK PERFORMED
☑ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☑ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☑ Rotary ☐ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Silty Sand w/gravel		0	10	10'
Sand w/trace "		10	18	8'
Sandy gravel		18	35	17'
Silty Sand w/gravel		35	63	28'
Rock - Diorite		63	66	3'
Silty Sand w/gravel		66	75	9'
Clayey Sand w/gravel		75	80	5'
Sandy Silt, trace gravel		80	85	5'
Silty Sand " "		85	89	4'
Clayey Sand		89	94	5'
Silty Sand, trace gravel		94	100	6'
Silty Sand		100	112	12'
Lean clay		112	135	23'
Clayey sand		135	155	20'
End of hole @ 155'				

Date started 6-1, 1992
Date completed 6-2, 1992

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

RECEIVED
AUG 13 1992
Div. of Water Resources
Branch Office - Las Vegas, NV

8. WELL CONSTRUCTION
Depth Drilled 155 Feet Depth Cased 148 Feet

HOLE DIAMETER (BIT SIZE)

	From	To
6 Inches	0 Feet	155 Feet
Inches	Feet	Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2"	.71 lbs	Sch. 80	0	148.

Perforations:
Type perforation factory slotted
Size perforation 0.020
From 108 feet to 148 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☑ Yes ☐ No
Depth of Seal 0-95 / Bent. 93-95
Placement Method: ☐ Pumped ☑ Poured
Seal Type: ☐ Neat Cement ☑ Cement Grout ☐ Concrete Grout

Gravel Packed: ☑ Yes ☐ No
From 95 feet to 148 feet

9. WATER LEVEL
Static water level 142. feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Don Wilson (Contractor)
Address 4670 S. Polaris Ave (Contractor)
Las Vegas, Nevada 89103
Nevada contractor's license number issued by the State Contractor's Board
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M1589
Signed (By driller performing actual drilling on site or contractor)
Date 8-13-92

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627